



# Troubleshooting with Concrete

- a Pre-mix Suppliers Perspective -



By: Joe Pietrosanto  
TJM Operations Pty Ltd  
Trading as: VIC MIX




# Introduction



Some typical problems faced by Concrete Suppliers:

n While tendering for supply;



n In the batch plant



n on the construction site;



and how they are resolved.


# Tendering for supply



n Verbal requirements / orders



n Written requirements / specifications



# Verbal Requirements / Orders




- n The majority of price enquiries are received verbally
- n Most jobs do not have a written specification.
- n Sometimes, the specification is a note on a working drawing
- n Often, the tender submission and review will take place in a single conversation which may result in concrete on site within the hour

When I said 4 "Meters",  
I meant "Concrete" !!!

The most common problem is:

- n Misunderstanding of important project details and requirements



# Handling Verbal requirements



- n Enquiries are received in a modern Call Centre
- n Computer systems control customer and project details
- n Customer Service staff are trained to communicate effectively



Typical Central Order Sales Office



Computerised Systems control  
Customer details, enquiries and orders

Environment, technology and training work to improve communication

# Written Specifications



All major projects have written specifications

The problems faced by Concrete Suppliers are:

- n Securing a current and complete copy of the Project Specifications from our potential Customers.
- n Interpreting the specification and designing concrete mixes to meet all relevant requirements.
- n Completing this entire process in as short a time frame as possible.

The Concrete Industry sells concrete like pizza. Product can be ordered and delivered within the hour.  
The ingredients are different for each order and the product must reach the Customer while it is still fresh



# Specification Requirements



Specifications often contain prescriptive and performance based requirements which aim to ensure the best possible concrete is supplied.

Problems arise for the Pre-mix Concrete Supplier when

- requirements conflict; or
- requirements are not practical or commonly accepted

The concrete shall not exhibit any shrinkage

The concrete produced will be allowed the following tolerances as required for workability:

	Tolerance for % passing
Aggregate passing 4.75mm sieve or larger	+/- 4
Aggregate passing 2.36mm to 0.6mm sieve	+/- 3
Aggregate passing 0.3mm sieve	+/- 2
Aggregate passing 0.15mm to 0.075mm sieve	+/- 1

Aggregates shall at all times be dealt with in such a way that the exact weight of any one size of aggregate may be incorporated in a batch of concrete in accordance with the approved design of a batch to meet the strength and density requirements.

The use of Fly Ash is strictly prohibited

No admixtures shall be incorporated

The number and rate of concrete slump tests shall be at the rate of one (1) test per truck.

Aggregates shall be delivered to the Concrete Plant at least 24 hrs before batching

Target slump for hand placed concrete shall not exceed 20mm

mix design shall match the attached combined particle size distribution

# Contract Review



- n The customer's pricing inquiry is reviewed to ensure that requirements are understood and to examine our capacity to meet them.
  - This process involves
    - n using experience and technology to meet the Customer's needs
    - n ensure that pricing is carried out in accordance with Company Policies
    - n ensuring we have the resources and capabilities to meet the requirements
    - n isolating requirements that cannot be complied with and resolving them prior to acceptance

*Address the project requirement*

Submission for supply of Concrete


*Submit the concrete mix designs*

*Submit the products and prices*

*Submit the conditions for supply*

Submit features or clarification with the specification

Submit the performance data





# Performance Testing



n Pre-mixed Concrete Suppliers are continuously expanding their testing capabilities to meet Customer requirements



Slump Testing



Air & Yield Testing



Compression Testing



Indirect Tensile Testing  
(Brazil or Splitting Test)



Core Testing



AVPV Testing



Shrinkage Testing



Flexural Testing  
(Modulus of Rupture)

# Problems at the Batch Plant



n Materials Contamination



n Batching tolerances



# Contamination in Raw Materials



Some objects recovered from concrete over the last couple of years



Wood

4 x 4 x 60 cm long

Probably a broken formwork stake  
Source unknown



Cast Iron

1 x 10 x 50 cm long  
twisted and corroded piece of iron

Source unknown



Aluminium plate

0.5 x 14 x 27 cm  
Heavy wear on one end

Source unknown



Clay Lump

Approximately 16 cm diameter

Contamination is most likely from the Sand Quarry Pit



Rock Spall

Approximately 10 cm diameter Hornfels rock

Contamination most likely occurred at the Quarry

# Reducing contamination



- n Improved Bin Systems fitted with grates to reduce the possibility of contaminants entering the production process

Ground bins allow multiple specialist aggregate products to be stored without contamination.



Concrete Plant Bins



The Grates prevent:

- people falling inside the bin
- as well as exposing and preventing large contaminants from entering the bin

# Batching Tolerances



- n Meeting batching tolerances are a prime concern for every concrete plant
- n AS1379 recognises that tolerance are a practical necessity and has set requirements for all concrete ingredients.
- n Errors in batching can alter the concrete's expected properties.

Some examples are:

- n Under batched cement may result in strength loss
- n Over or under dosed admixture may result in setting time variability
- n Over batched coarse aggregate may result in reduced pumpability
- n etc.

# Ensuring tolerances are met




- n Computers control batching and ensure tolerances are met
- n Regular maintenance and calibration of equipment reduces the number of plant malfunctions


Computer systems



Equipment maintenance



Calibration Records



# Problems on site



n Placeability and Pumpability



n Concrete Bleeding and setting time




n Concrete Defects



# Placeability and Pumpability



- n Placeability and pumpability is generally dictated by the following:
  - n Consistency or slump
  - n Volume of fines
  - n Size, shape and texture of coarse aggregates
- n Placeability and pumpability is generally improved by:



Increase in slump/consistency



Increase in paste volume



Increase in roundness  
Decrease in size of aggregate



# Pumping Lightweight




- n Significant cost savings are enabled with the use of lightweight concrete in the construction of highrise buildings.
- n However, Lightweight can be difficult to pump and place successfully.
- n Two factors are the most challenging when using lightweight in high rise construction
  - n The aggregate; and
  - n The vertical pumping distance.



Highly vesicular porous rock  
Typically 1600 kg/m<sup>3</sup>



Highrise Construction



# Pumping Lightweight



- n The key to pumping porous vesicular aggregates is pre-treatment at the Concrete Plant
- n Water sprays keep the aggregate saturated

The result is:

lightweight concrete capable of being pumped more than 25 floors in height.



IBM & HWT City Road



222 Russell Street

# Concrete Bleeding



- n Bleeding is the name given to the action of water rising to the top of concrete shortly after compaction. Factors which affect bleeding are:
  - n Rate of evaporation
  - n Consistency or slump
  - n Volume of fines in the mix



- n Bleeding is generally reduced by:
  - n An increase in temperature and the evaporation rate (ie summer time)
  - n A reduction in the water content of the mix
  - n An increase in the ultra fines content of the mix
  - n The use of specialist admixtures (ie Air Entrainers, fibres)

# Concrete Setting Time




- n Setting Time describes the period of time it take for the concrete to stiffen and harden. Factors which affect setting time are:
  - n Temperature of concrete

# Concrete Setting Time



## n Graphed temperature data

– based on field tests performed on concrete in the field.



# Concrete Setting Time



- n Setting Time describes the period of time it take for the concrete to stiffen and harden. Factors which affect setting time are:
  - n Temperature of concrete
  - n Quantity of mixing water
  - n Type of cements used in the concrete
  - n The presence of admixtures
  
- n Setting time is generally reduced by:
  - n An increase in the concrete temperature (ie summer time)
  - n A reduction in mix water (ie reduce slump)
  - n The use of primary cementitious binders
  - n The use of non-chloride set accelerating admixtures

# Concrete Defects



- n The vast majority of complaints relate to defects in flatwork
  - n Scaling
  - n Dusting
  - n Cracking
  
- n Most of these defects can be reduced or eliminated with the appropriate site practices
  
- n Prevention is always better than a cure



# Concrete Scaling



- n Scaling, blistering, delamination is when the outer surface of the concrete peels or pops off in a thin layer
  - n the depth of the defect is shallow
  - n it typically occurs under conditions of high surface evaporation




- n Things to watch out for:
  - n Don't allow the surface to dry out. This may form a skin under which bleed water and air can become trapped
  - n Don't add water to the surface during finishing. This may re-hydrate the past, but leads to separation from the underlying concrete
  - n Protect the surface from drying out and apply even continuous curing asap



# Concrete Dusting



- n Dusting is characterised by the appearance of a fine powder as the surface wears under very light loading conditions
  - n the defect is limited to the outer surface of the concrete
  - n low cement content mixes are more susceptible



- n Things to watch out for:
  - n Do not perform any finishing operations while bleed water is on the surface
  - n Be wary of additional bleed due to placement over a non-absorptive subgrade
  - n Ensure the surface is protected from drying conditions
  - n Apply even continuous curing asap

# Plastic Cracking



- n Cracks which occur in the first few hours after placing as the concrete stiffens
  - n often not visible or noticeable until the next day
  - n most common in flat work under conditions of high evaporation



- n Things to watch out for:
  - n Remember to dampen the subgrade and forms during hot weather
  - n Erect wind breaks and spray aliphatic alcohol on the surface
  - n begin even continuous curing as soon as possible
  - n avoid placing concrete on hot, windy days

# End of Presentation



n Thankyou for your attention

